EAML 58 F - 63 F / G ANALOGUE

BLIND HOLLOW SHAFT MULTITURN ABSOLUTE ENCODER

MAIN FEATURES

Industry standard multiturn absolute encoders for factory automation applications.

- Optical/magnetic (proprietary optoASIC + energy harvesting) sensor technology
- Programmable measuring range via teach-in function (external inputs or cover button)
- Power supply up to +30 VDC with analogue (voltage or current) electrical interface
- Cable or M12 connector output
- Blind hollow shaft up to 15 mm
- Mounting by stator coupling, torque stop slot or torque pin

ORDERING CODE	EAML	58F	16B	12/30	V	05	X	15	X	M12	R	.162	+XXX

SERIES
analogue multiturn absolute encoder EAML

MODEL
blind hollow shaft with stator coupling 58F
blind hollow shaft with torque stop slot 63F
blind hollow shaft with torque pin 63G

OUTPUT DAC RESOLUTION
16 bit 16B

POWER SUPPLY
12 ... 30 V DC 12/30

ELECTRICAL INTERFACE
voltage V
current I

OUTPUT RANGE
0 ... 5 V 05
0 ... 10 V 010
0 ... 20 mA 020
4 ... 20 mA 420

OPTIONS
to be reported with voltage output / 3 wires current output X
4 wires current output Q

BORE DIAMETER
mm 14
mm 15
diameters 6 / 8 / 9,52 (3/8") / 10 / 11 / 12 mm with optional shaft adapter, see Accessories

ENCLOSURE RATING
IP 65 shaft side / IP67 cover side X
IP 67 S

OUTPUT TYPE
cable (standard length 1,5 m) P
preferred cable lengths 2 / 3 / 5 / 10 m, to be added after DIRECTION TYPE (eg. PR5)
M12 plug connector M12

DIRECTION TYPE
radial R

SOCKET
socket not included .162
to be reported only with connector output (eg. M12R.162), for socket see Accessories

VARIANT
custom version XXX

© Copyright 2025 Eltra S.p.a. Unipersonale. All rights reserved. All informations in this catalog are subject to change without notice.
Eltra takes no responsibility for typographic errors. For the terms of sales please check the website. REV. 2502

eltra.it@broadcom.com

58F



63F



for torque pin please refer to Accessories

63G



torque pin is included

recommended mating shaft tolerance g6

dimensions in mm

© Copyright 2025 Eltra S.p.a. Unipersonale. All rights reserved. All informations in this catalog are subject to change without notice.
Eltra takes no responsibility for typographic errors. For the terms of sales please check the website. REV. 2502

ELECTRICAL SPECIFICATIONS

Multiturn resolution	16 bit max
Singleturn resolution	16 bit max
Output DAC resolution	16 bit
Minimum angle	22,5°
Power supply[1]	11,4 ... 30 V DC (reverse polarity protection)
Power draw without load	< 1 W
Electrical interface[2]	voltage (0 ... 5 V / 0 ... 10 V) current (0 ... 20 mA / 4 ... 20 mA)
Auxiliary inputs (BEGIN - END)	active high (+V DC) connect to 0 V if not used / t_{min} 150 ms
Load	R_{min} = 1 kΩ (voltage output) R_{max} = (V DC - 2) / 0,02 (current output)
Output update frequency	16 kHz
Signal pattern	auto teaching according to commissioning
Start-up time	700 ms
Linearity error	± 0,069°
Mean time to dangerous failure ($MTTF_d$)[3] according to EN ISO 13849-1	186 years
Mission time (Tm)[3]	20 years
Diagnostic coverage (DC)[3]	0%
Cable type	shielded - fixed installation conductors section 0,22 mm² / AWG 24 bending radius min 60 mm
Electromagnetic compatibility	according to 2014/30/EU directive
RoHS	according to 2011/65/EU directive
UL / CSA	file n. E212495

ELECTRICAL INTERFACE

VOLTAGE OUTPUT



CURRENT OUTPUT



3 / 4 wire source
with 3 wires interface Iin is internally connected to 0V

MECHANICAL SPECIFICATIONS

Bore diameter	ø 14 / 15 mm ø 6 / 8* / 9,52 (3/8")* / 10* / 11* / 12* mm * with optional shaft adapter, please refer to Accessories
Enclosure rating IEC 60529	X = IP 65 shaft side / IP67 cover side S = IP 67
Max rotation speed	see table
Max shaft load[4]	200 N (45 lbs) axial / 60 N (13,49 lbs) radial
Shock	50 G, 11 ms (IEC 60068-2-27)
Vibration	10 G, 10 ... 2000 Hz (IEC 60068-2-6)
Moment of inertia	5 x 10^{-6} kgm² (119 x 10^{-6} lbft²)
Starting torque (at +20°C / +68°F)	< 0,03 Nm (4,25 Ozin)
Bearing stage material	aluminum
Shaft material	stainless steel
Housing material	painted aluminium
Bearings	n.2 ball bearings
Bearings life	10^9 revolutions
Operating temperature [5, 6]	-20° ... +85°C (-4° ... +185°F)
Storage temperature[6]	-20° ... +85°C (-4° ... +185°F)
Weight	approx 350 g (12,35 oz)

[1] as measured at the transducer without cable influences
[2] for further details refer to OUTPUT LEVELS on TECHNICAL BASICS section
[3] this product is not a safety component, for further details refer to TECHNICAL BASICS section
[4] maximum load for static usage
[5] measured on the transducer flange
[6] condensation not allowed

ROTATION SPEED / TEMPERATURE TABLE

Temperature °C (°F)	Max speed (rpm)	Max continuous speed (rpm)
up to +70 (+158)	10000	8000
+70 ... +85 (+158 ... +185)	8000	5000

CONNECTIONS

Function	Cable	5 pin M12	8 pin M12*
+ V DC	red	2	2
0 V	black	3	3
V_{out} / I_{out}	green	1	1
I_{in}	yellow	/	6
BEGIN	white	4	4
END	brown or grey	5	5
⏚	shield	housing	housing

* with Q current ouput

M12 connector (5 pin)
M12 A coded
front view



M12 connector (8 pin)
M12 A coded
front view



© Copyright 2025 Eltra S.p.a. Unipersonale. All rights reserved. All informations in this catalog are subject to change without notice.
Eltra takes no responsibility for typographic errors. For the terms of sales please check the website. REV. 2502

eltra.it@broadcom.com