EMI 63 A / D / E

SOLID SHAFT MAGNETIC INCREMENTAL ENCODER

MAIN FEATURES

Standard ø 63 mm encoder series for industrial applications with high mechanical resistance requirements. Based on a proprietary magnetic sensor these encoders are designed to withstand high radial and axial shaft loads and can be mounted by flanges or fixing clamps.

- 3 channel encoder (A / B / Z) up to 10000 ppr
- Power supply up to +30 V DC with various electrical interfaces available
- Output frequency up to 800 kHz
- Cable or connector output
- Metal cover availablefor heavy duty applications
- Solid shaft diameter up to 10 mm
- Mounting by synchronous or centering 2,5" square flange



ORDERING CODE	EMI	63A	M*	500	S	5/30	P	8	X	X	M	R	.162	+XXX

SERIES
magnetic incremental encoder series EMI

MODEL
synchronous flange ø 31,75 mm 63A
centering square flange ø 31,75 mm 63D
centering square flange ø 50 mm 63E

METAL COVER
* add for metal cover M

RESOLUTION
ppr from 1 to 10000
please refer to the preferred resolutions list

ZERO PULSE
without zero pulse S
with zero pulse Z

POWER SUPPLY
(with L electrical interface) 5 V DC 5
5 ... 30 V DC 5/30

ELECTRICAL INTERFACE
NPN open collector C
push-pull P
line driver L
power supply 5/30 V DC - output RS-422 RS

SHAFT DIAMETER
mm 8
(3/8") mm 9,52
mm 10

ENCLOSURE RATING
IP 54 X
IP 66 S

OPTION
to be reported X

OUTPUT TYPE
cable (standard length 1,5 m) P
preferred cable lengths 2 / 3 / 5 / 10 m, to be added after DIRECTION TYPE (eg. PR5)
MIL plug connector M
JIS-C-5432 IP40 plug connector J
M12 plug connector M12
M23 plug connector H
M16 IP40 plug connector C

DIRECTION TYPE
axial A
radial R

SOCKET
socket not included .162
to be reported only with connector output (eg. MR.162), for socket see Accessories

VARIANT
custom version XXX

© Copyright 2025 Eltra S.p.a. Unipersonale. All rights reserved. All informations in this catalog are subject to change without notice.
Eltra takes no responsibility for typographic errors. For the terms of sales please check the website. REV. 2502

63A



fixing clamps not included, please refer to the Accessories

63D



63 E



recommended mating shaft tolerance H7
dimensions in mm

DIMENSION WITH METAL COVER AND AXIAL OUTPUT



DIMENSION WITH METAL COVER AND RADIAL OUTPUT



© Copyright 2025 Eltra S.p.a. Unipersonale. All rights reserved. All informations in this catalog are subject to change without notice.
Eltra takes no responsibility for typographic errors. For the terms of sales please check the website. REV. 2502

eltra.it@broadcom.com

ELECTRICAL SPECIFICATIONS

Resolution	from 1 to 10000 ppr
Power supply[1]	5 = 4,5 ... 5,5 V DC 5/30 = 4,5 ... 30 V DC (reverse polarity protection)
Power draw without load	0,8 W max
Max load current	C / P = 50 mA / channel L / RS = 20 mA / channel
Electrical interface[2]	NPN open collector (AEIC-7273, pull-up max +30 V DC) push-pull / line driver HTL (AEIC-7272 or similar) line driver RS-422 (AELT-5000 or similar)
Max output frequency	800 kHz
Counting direction	A leads B clockwise (shaft view)
Index signal	180°e (gated A)
Startup time typical	20 ms
Accuracy	< 0,2° at +20°C (+68°F) ± 0,5° in the operating temperature range
Hysteresys	0,70° up to 256 ppr 0,35° from 257 ppr to 10000 ppr
Mean time to dangerous failure ($MTTF_d$)[3] **according to EN ISO 13849-1**	275 years
Mission time (Tm)[3]	20 years
Diagnostic coverage (DC)[3]	0%
Cable type	shielded - fixed installation conductors section 0,22 mm² / AWG 24 bending radius min 60 mm
Electromagnetic compatibility	according to 2014/30/EU directive
RoHs	according to 2011/65/EU directive
UL / CSA	file n. E212495

MECHANICAL SPECIFICATIONS

Shaft diameter	ø 8 / 9,52 (3/8") / 10 mm
Enclosure rating IEC 60529	X = IP 54 S = IP 66
Max rotation speed	6000 rpm
Max shaft load[4]	200 N (45 lbs) axial / radial
Shock	50 G, 11 ms (IEC 60068-2-27)
Vibration	10 G, 10 ... 2000 Hz (IEC 60068-2-6)
Moment of inertia	1,5 x 10^{-6} kgm² (36 x 10^{-6} lbft²)
Starting torque (at +20°C / +68°F)	< 0,02 Nm (2,83 Ozin) with X enclosure rating < 0,06 Nm (8,50 Ozin) with S enclosure rating
Bearing stage material	aluminum
Shaft material	stainless steel
Housing material	PA66 glass fiber reinforced / painted aluminum
Bearings	n.2 ball bearings
Bearings life	10^9 revolutions
Operating temperature[5, 6]	-25° ... +100°C (-13° ... +212°F) -25° ... +85°C (-13° ... +185°F) with M12 connector
Storage temperature[6]	-25° ... +70°C (-13° ... +158°F)
Weight	350 g (12,35 oz) 450 g (15,87 oz) with metal cover

[1] as measured at the transducer without cable influences
[2] for further details refer to OUTPUT LEVELS on TECHNICAL BASICS section
[3] this product is not a safety component, for further details refer to TECHNICAL BASICS section
[4] maximum load for static usage
[5] measured on the transducer flange
[6] condensation not allowed

PREFERRED RESOLUTIONS

2 - 4 - 5 - 6 - 8 - 10 - 12 - 16 - 20 - 30 - 40 - 50 - 60 - 80 - 90 - 100 - 125 - 128 - 200 - 250 - 256 - 360 - 400 - 500 - 512 - 720 - 1000 - 1024 - 1440 - 2000 - 2048 - 3600 - 4096 - 5000 - 7200 - 10000

please directly contact our offices for other pulses

CONNECTIONS

Function	Cable C / P	Cable L / RS	7 pin J C / P	7 pin J L / RS no Zero	7 pin M C / P	7 pin M L / RS no Zero	10 pin J L / RS with Zero	10 pin M L / RS with Zero	5 pin M12 C / P	8 pin M12 L / RS	12 pin H	5 pin C C / P	8 pin C L / RS
+V DC	red	red	6	4	F	D	4 - 5	D - E	2	7	12	5	7
0 V	black	black	1	6	A	F	6	F	4	1	10	1	8
A+	green	green	3	1	C	A	1	A	3	6	5	2	1
A-	/	brown or grey	/	3	/	C	7	G	/	5	6	/	2
B+	yellow	yellow	5	2	E	B	2	B	1	4	8	4	3
B-	/	orange	/	5	/	E	8	H	/	3	1	/	4
Z+	blue	blue	4	/	D	/	3	C	5	2	3	3	5
Z-	/	white	/	/	/	/	9	I	/	8	4	/	6
⏚	shield	shield	7	7	G	G	10	J	housing[1]	housing[1]	9	housing[1]	housing[1]

[1] only with metal cover

J connector (7 pin)
JIS-C-5432 IP40 Size 16
front view



M connector (7 pin)
Amphenol MS3102-E-16-S
front view



M12 connector (5 pin)
M12 A coded
front view



C connector (5 pin)
Amphenol C091 M16 IP40
front view

H connector (12 pin) - M23 CCW
Hummel 7.410.000000 - 7.002.912.603
front view

J connector (10 pin)
JIS-C-5432 IP40 Size 16
front view



M connector (10 pin)
Amphenol MS3102-E-18-1
front view



M12 connector (8 pin)
M12 A coded
front view



C connector (8 pin)
Amphenol C091 IP40 IEC 60130-9
front view

© Copyright 2025 Eltra S.p.a. Unipersonale. All rights reserved. All informations in this catalog are subject to change without notice.
Eltra takes no responsibility for typographic errors. For the terms of sales please check the website. REV. 2502